

## APPENDIX A, SHELTER PRODUCT DATA SHEET, REVISION A:

PRODUCT DATA SHEET		CONTRACTOR NAME: CAMSS Shelters				
1.PART NUMBER: C	AMSS-HIT-2	0QSAG		2.NSN:		
3.NAME: CAMSS20SA Billeting		4.TYPE: Billeting S		helter System	5.CLASS:	
6.COLOR: 483 Olive Drab		7. Support System: Frame			8.SERIES: CAMSS20Q	
9. INTENDED USE: E	Billeting, Com	mand Post,	General F	Purpose for heavy	snow and wind load areas	
10.DIMENSIONS (IN FEET AND INCHES)	LENGTH: 32'6"		WIDTH: 20'		HEIGHT: RIDGE/EAVE: 10' Peak Height	
11.DIMENSIONS (EXTERNAL GUYED)	LENGTH: 32'6"		WIDTH 26'			
12.SQUARE FEET IN 632 Square Feet	TERIOR:					
13.WEIGHT (POUNDS, UNPACKAGED) 1,240 lbs			14.WEI (PACK) 1,640 Ik	AGED)	15.SHIPPING CUBE (PACKAGED) 75 cu. ft	
16SHIPPING CONTAINER	LENGTH: 102"		WIDTH: 44"		HEIGHT: 29"	
		·	NUMBE		15 minutes/4 persons	
19 PARTS INCLUDED	The CAMSS	s ai A2000	complete	a chaltare evetan	that includes an aluminum frame	

19.PARTS INCLUDED: The CAMSS20QSA is a complete shelters system that includes an aluminum frame, tensioned MIL Spec fabric cover system, fabric floor, extreme temperature kit, quick connect electrical system with lights, outlets and a distribution panel that meet UL and NEC standards. Also included is an anchoring package with double headed spikes, guy spikes and guy ropes and a repair kit. The complete CAMSS20QSA is packed in a wooden crate. Both composite and rotationally molded containers are optional items.

20.DESCRIPTION: The CAMSS20QSA billeting shelter is a quonset style shelter system used for billeting in extreme environments worldwide. The CAMSS20SA uses a 2" x 3" aluminum frame to meet a 20PSF snow load per TOP 10-2-175 and a 100 mph wind load. The CAMSS20QSA includes one aluminum hard door and one double zipper door. The cover system includes ten windows on the cover and two on each end The CAMSS shelter is compatible with existing military fluorescent lighting systems. Optional lights in accordance with MIL-L-44259 are available. It may be connected to a TEMPER vestibule and it is supported by optional trailer systems with generators and ECUs.

21. SUPPORT EQUIPMENT:	PART NUMBER Or NSN	Included or Optional	
LIGHT SET Product Data Sheet	HIT-20Q-ELC01	Included	Incandescent Light Strings
	HIT-20Q-ELC01-LED	Optional	Light String with LED light bulbs
	HIT-20Q-ELC01-CFL	Optional	Light String with CFL light bulbs
ELECTRICAL OUTLET SET Product Data Sheet	HIT-20Q-ERPL02	Included	Triplex Outlets – Long
	HIT-20Q-ERPS02	Included	Triplex Outlets – Short
FLOORING	CANACCZOO DELOA	lie eli i el e el	Tabaia Cananith and a fault and a declarate de
Product Data Sheet	CAMSS20Q-PFL01	Included	Fabric floor with cutouts for base stubs and Velcro to attach to cover
	CAMSS-HFLD/SF	Optional	hard plastic flooring
HEATER			

Product Data Sheet			
AIR CONDITIONER Product Data Sheet	CAMSS-5TECU01	Optional	Five ton ECU with 12kw of heating
	CAMSS-2.5TECU01 Optional		2.5 ton ECU with 12kw of heating
GENERATOR Product Data Sheet	CAMSS-G20KW	Optional	20Kw Generator
POWER DISTRIBUTION Product Data Sheet	CAMSS-E2SPDS	   Optional	Two shelter power distribution system
TRAILER MOUNTED	CAMSS-LTT-LE	Optional	CAMSS Light Tactical Trailer System
SUPPORT SYSTEM Product Data Sheet			
INSULATED LINER Product Data Sheet	CAMSS20Q-HLLE	Optional	CAMSS Insulcam liner system installs quickly and easily like the basic liner system and reduces demand on ECUs by 42%
INSULATED FLOORING Product Data Sheet			
SOLAR SHADE/ CAMOU. NETT Product Data Sheet	CAMSS20Q-PSF01	Optional	CAMSS Solar Fly is a unique fly system that slides over the cover and reduces solar load on the shelter.